

Upgrade your existing rotary tool to 4.3 times the speed!

Speed-Increasing Spindle for CNC Automatic Lathes

NGS-3140-CTZ01

Tool clamping diameter: $\phi 0.5$ to $\phi 6.35$ mm

This product can be mounted on the rotating tool unit of a CNC automatic lathe and rotates using the machine's power. Compared to conventional rotating tools, it can achieve a maximum of 4.3 times faster rotation.

It maximizes the machining range of CNC automatic lathes.


This spindle incorporates Nakanishi's advanced motor spindle technology.



Machining data




$\phi 3 \times 6.4$ mm Through-hole drilling		$\phi 4$ end mill Side cutting	
Workpiece	A6061 (Aluminum alloy)	Workpiece	A6061 (Aluminum alloy)
Tool	Mitsubishi Materials Corp MVE0300X03S030	Tool	NS Tool Co., Ltd. ALZ345 $\phi 4.0 \times 12$ mmL
Hole depth	6.4 mm through-hole	Depth of cut ($A_p \times A_e$)	5 mm $\times$ 0.8 mm
Cutting speed	94 m/min	Cutting speed	251 m/min
Rotational speed	10,000 min ⁻¹	Rotational speed	20,000 min ⁻¹
Feed per rev.	0.16 mm/rev	Feed per blade	0.017 mm/tooth
Feed rate	1,600 mm/min	Feed rate	1,000 mm/min



Specifications

Code No.: 7915

Model: NGS-3140-CTZ01



O.D.	Allowable rotational speed	Spindle accuracy	Net weight
φ31 mm	Machine command speed 10,000 min ⁻¹ : 43,000 min ⁻¹	Within 1 μm	582 g
Standard equipment and accessories	Collet nut (K-265) / Wrench (12 × 14): 2 pcs. Hexagon socket bolt (M5 × 30): 4 pcs. / Grease dispenser / Grease nipple *Collet is sold separately.		
Replaceable rotary tool	GSC1310 (manufactured by Citizen Machinery Co., Ltd.)		
Applicable CNC Lathes	A20, D25, L20, L32, M32, etc.		

Combination example

Collet	Spindle	Applicable CNC Lathes
 CHK φ0.5-φ6.35 mm	 NGS-3140-CTZ01	Citizen Machinery Co., Ltd. A20, D25, L20, L32, M32, etc. (Replaceable rotary tool: GSC1310)

Machining conditions

■ φ2.5 drilling

Processing method	Workpiece	Tool	Cutting speed [m/min]	Rotational speed [min ⁻¹]	Feed per rev. [mm/rev]	Feed rate [mm/min]
Conventional drilling (Standard rotary tool)	S50C (Carbon steel)	Mitsubishi Materials DWAE0250X04S040 φ2.5	39	5,000	0.08	400
Nakanishi's proposed conditions			94	12,000	0.05	600

Feed rate
improved by
150%!

■ φ3.0 end mill machining

Processing method	Workpiece	Tool	Cutting speed [m/min]	Rotational speed [min ⁻¹]	Feed per blade [mm/tooth]	Feed rate [mm/min]	Depth of cut Ap × Ae [mm]
Side cutting	S50C (Carbon steel)	Mitsubishi Materials MS2ES φ3.0	132	14,000	0.03	750	0.3 × 2.7



NAKANISHI INC.
Headquarters

700 Shimohinata, Kanuma, Tochigi 322-8666, Japan
TEL: +81-289-64-3520 / FAX: +81-289-62-1135

en.nakanishi-spindle.com
NAKANISHI INC. 2025

PR-K424E Ver.1 2025-12-19 XXX.YX [XXX]

